



尖端的真空设备 铂杉产品选型手册

姓名:夏目

微信:boshanxiamu

电话:185-6656-3069

邮箱:xiamu@boshanvac.com

网址:www.boshanvac.com

地址:东莞市寮步镇寮步坑口桃苑4巷8号

营业联系



nEDC干式爪泵



nEDC系列是单爪式真空泵的最新迭代版本。它具备一系列创新特性，这些特性不仅能够提升性能，而且还能降低噪音水平、提高可靠性并便于现场进行简易维护。

严苛的工业应用环境需要一种能够耐受恶劣操作条件的泵。nEDC系列最新一代干式爪泵确保了可靠运行、易于维护且成本低廉。该产品结构坚固、性能高效，且完全符合我们客户所要求的严苛标准和质量标准。为您提供了一个无故障且经济高效的解决方案以满足您的需求。

产品特点


模块化设计确保整个运行生命周期内的效率，同时实现IE4电机的卓越效率。

nEDC爪泵可轻松现场清洗，且由于内部采用无接触结构，减少磨损，无需频繁维护。

这些新一代泵内部温度较低，延长唇口密封寿命并防止漏油。

该泵的爪子具有高度耐腐蚀性，配有涂层泵送腔，以防止部件损坏。

你需要的全部功率同时降低噪音——nEDC真空泵采用了重新设计的消音器，可以减少机器噪音。



技术数据

真空数据	nEDC 65	nEDC 150	nEDC 300
峰值抽速 (m3h1)	65	150	300
极限真空 (mbar)	50	50	140
电机功率 (KW)	1.7	3.8	6.2
电机转速 (rpm)	3600	3600	3600
噪音 (db)	66	66	72
注油量 (L)	1.5	1.5	1.5
进气口链接尺寸	G1 ¼" or NPT	G2" or NPT	G1 ¼" or NPT
出气口连接尺寸	G1 ¼" or NPT	G1 ¼" or NPT	G1 ¼" or NPT
泵启动环境温度	0-40°C	0-40°C	0-40°C

- 1、测量的是全压力
- 2、如需获取更多详细资料请联系技术支持
- 3、技术电话：夏目 185-6656-3069



24小时为客户提供服务

高效率

高品质

高服务

除了拥有出色的性能、效率及实用性的真空设备，我们也可以提供精湛的服务和支持。无论是在我们的服务中心还是您的现场，我们均可为多个品牌和应用提供服务。可以快速响应您的需求，就算是不间断工艺，也可让您安心生产。

In addition to vacuum equipment with excellent performance, efficiency, and practicality, we can also provide exquisite servicesService and support. Whether in our service center or on your site, we can serve multiple brands and applicationsProvide services. We can quickly respond to your needs, even with uninterrupted processes, allowing you to produce with peace of mind.

你想了解更多吗？

请直接联系我们！

电话：185-6656-3069

邮箱：xiamu@boshanvac.com



在线客服



营业联系